

Driven by innovation, Defined by Quality



www.zenonpetroleum.ae

Zenon Petroleum FZE is a premier lubricant manufacturing company based in Hamriyah Free Zone, Sharjah, UAE. Since its inception, Zenon Petroleum has been committed to delivering high-performance lubricants tailored for the GCC, Middle East, Far East, and African markets, combining regional expertise with international quality standards.

At Zenon Petroleum, we recognize that knowledge and experience are the keys to excellence. Our team consists of industry veterans, strategic partners, and technical specialists who drive innovation and ensure our products meet the evolving demands of the global automotive and industrial sectors.

We utilize advanced automated blending technology and precision machinery to produce lubricants that are consistent, reliable, and free from human error. This approach allows us to maintain strict quality control while ensuring on-time delivery for our clients.

Our lubricants are crafted from top grade virgin base oils and premium additives, engineered to meet the most stringent industry standards. With Zenon Petroleum, customers can expect superior performance, enhanced equipment protection, and long-term reliability in every product we deliver.



Passenger Car Motor Oil

ZENON PRO

Enhanced Engine Protection

High Performance Formula



0W-16

API SP
ACEA A3/B4



DESCRIPTION

ZENON PRO 0W-16 is a fully Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON PRO 0W-16 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.860
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	7.4
Viscosity Index	ASTM D2270	-	160
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-39

Package (Liters) 1L, 4L, 5L, 20L, 208L

0W-20

API SP
ACEA A3/B4

DESCRIPTION

ZENON PRO 0W-20 is a Fully Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON PRO 0W-20 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.860
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	8.9
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-39

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Package (Liters) 1L, 4L, 5L, 20L, 208L

0W-30

API SP
ACEA A3/B4



DESCRIPTION

ZENON PRO 0W-30 is a fully Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON PRO 0W-30 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.5
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-36

Package (Liters) 1L, 4L, 5L, 20L, 208L

0W-40

API SP
ACEA A3/B4

DESCRIPTION

ZENON PRO 0W-40 is a fully Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON PRO 0W-40 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.860
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	13.8
Viscosity Index	ASTM D2270	-	160
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-39

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Package (Liters) 1L, 4L, 5L, 20L, 208L

5W-30

API SP
ACEA A3/B4



DESCRIPTION

ZENON PRO 5W-30 is a fuel-efficient fully Synthetic Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.5
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-36

Package (Liters) 1L, 4L, 5L, 20L, 208L

5W-40

API SP/CK-4
ACEA A3/B4

DESCRIPTION

ZENON PRO 5W-40 is a fuel-efficient fully Synthetic Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.



Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	14.2
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Package (Liters) 1L, 4L, 5L, 20L, 208L

Passenger Car Motor Oil **ZENON NEO**

Advanced Engine Protection

Next-Gen Performance



0W-16

API SN/CF
ACEA A3/B4



DESCRIPTION

ZENON NEO 0W-16 is an ultra-low Viscosity Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON NEO 0W-16 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Package (Liters) 1L, 4L, 5L, 20L, 208L

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.860
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	7.4
Viscosity Index	ASTM D2270	-	160
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-39

0W-20

API SN/CF
ACEA A3/B4

DESCRIPTION

ZENON NEO 0W-20 is an ultra-low Viscosity Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON NEO 0W-20 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.860
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	8.9
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-39

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety

Package (Liters) 1L, 4L, 5L, 20L, 208L

0W-30

API SN/CF
ACEA A3/B4

DESCRIPTION

ZENON NEO 0W-30 is an ultra-low Viscosity Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON NEO 0W-30 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.



Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.5
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-36

Package (Liters) 1L, 4L, 5L, 20L, 208L

0W-40

API SN/CF
ACEA A3/B4

DESCRIPTION

ZENON NEO 0W-40 is an ultra-low Viscosity Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON NEO 0W-40 is especially recommended for vehicles equipped with start/stop systems.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

Recommended for modern Gasoline and Diesel passenger vehicles.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	14.2
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety

Package (Liters) 1L, 4L, 5L, 20L, 208L

5W-30

API SN/CF
ACEA A3/B4



DESCRIPTION

ZENON NEO 5W-30 is a fuel-efficient Synthetic Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

Recommended for Gasoline and Diesel vehicles, including those equipped with turbocharged engines.

Customer Benefits

- Excellent low-temperature performance for smooth cold starts
- Strong protection against wear and friction
- Reliable lubrication at both high and low operating temperatures
- Helps maintain engine cleanliness and efficiency

Package (Liters) 1L, 4L, 5L, 20L, 208L

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.5
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-36

5W-40

API SN/CF
ACEA A3/B4

DESCRIPTION

ZENON NEO 5W-40 is a fuel-efficient Synthetic Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

Recommended for Gasoline and Diesel vehicles, including those equipped with turbocharged engines.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	14.2
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Customer Benefits

- Excellent low-temperature performance for smooth cold starts
- Strong protection against wear and friction
- Reliable lubrication at both high and low operating temperatures
- Helps maintain engine cleanliness and efficiency

Package (Liters) 1L, 4L, 5L, 20L, 208L

10W-30

API SN/CF
ACEA A3/B4



DESCRIPTION

ZENON NEO 10W-30 is a synthetic engine oil with advanced synthetic technology to provide superior engine protection. It keeps engines cleaner by minimizing sludge and deposits, while the high-performance formulation ensures excellent wear protection and optimal lubrication. Its suitable high performance Gasoline engine and light duty Gasoline engine. designed for sever and continues driving conditions throughout the oil change interval.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Heavy-duty diesel engines (naturally aspirated & turbocharged)
- Gasoline engines requiring SAE 10W-30
- Mixed fleets: trucks, buses, construction & light commercial vehicles
- Engines operating under high load and high temperature conditions

Customer Benefits

- Outstanding wear protection for extended engine life
- Excellent piston deposit and sludge control
- High oxidation stability for longer oil life
- Strong viscosity retention under severe conditions
- Reliable performance across a wide temperature range

Package (Liters) 1L, 4L, 5L, 20L, 208L

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.7
Viscosity Index	ASTM D2270	-	145
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

10W-40

API SN/CF
ACEA A3/B4

DESCRIPTION

ZENON NEO 10W-40 is a synthetic engine oil with advanced synthetic technology to provide superior engine protection. It keeps engines cleaner by minimizing sludge and deposits, while the high-performance formulation ensures excellent wear protection and optimal lubrication. Its suitable high performance Gasoline engine and light duty Gasoline engine. designed for sever and continues driving conditions throughout the oil change interval.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

Recommended for Gasoline and Diesel vehicles.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.875
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15.3
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Customer Benefits

- Outstanding wear cleanliness
- Prevents sludge and deposits for smooth operation
- Minimizes engine friction to deliver maximum fuel efficiency
- Ensures quick lubrication in low temperatures

Package (Liters) 1L, 4L, 5L, 20L, 208L

15W-40

API SN/CF
ACEA A3/B4

DESCRIPTION

ZENON NEO 15W-40 is a Synthetic multi-grade Engine Oil designed for both Diesel and Gasoline engines operating under severe conditions with high-quality base oils and advanced additive technology, it provides excellent wear protection, high thermal stability, and superior detergency to keep engines clean and efficient.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Heavy-duty Diesel Engines (naturally aspirated & turbocharged)
- Gasoline engines requiring 15W-40
- Mixed fleets: Trucks, Buses, Construction & Light commercial vehicles
- Engines in high-load & high-temperature conditions

Customer Benefits

- Outstanding wear protection for extended engine life
- Excellent piston deposit and sludge control
- High oxidation stability for longer oil life
- Strong viscosity retention under severe conditions
- Reliable performance across a wide temperature range

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.875
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15.7
Viscosity Index	ASTM D2270	-	140
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-30

Package (Liters) 1L, 4L, 5L, 20L, 208L

20W-50

API SL/CF

DESCRIPTION

ZENON NEO 20W-50 is a High-quality, semi synthetic/mineral, Engine Oil formulated for Gasoline and Diesel Engines operating under severe driving conditions. Its thicker Viscosity provides a strong lubricating film that ensures excellent wear protection, reduced oil consumption, and reliable performance in High-temperature environments. It is particularly suitable for older Vehicles, Motorcycles, and Engines operating in hot climates.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Gasoline and Diesel Engines requiring 20W-50.
- High-performance and older Engines that need extra wear

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.875
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15.3
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Customer Benefits

- Strong oil films ensure superior wear protection under heavy loads
- Excellent high-temperature stability and oxidation resistance
- Reduced oil consumption and minimized deposits
- Enhanced protection for engines operating in hot climates

Package (Liters) 1L, 4L, 5L, 20L, 208L



Passenger Car Motor Oil

ZENON ECO

Eco Engine Efficiency

Smart Protection



5W-30

API SL/CF
ACEA A3/B4



DESCRIPTION

ZENON ECO 5W-30 is a fuel-efficient Semi Synthetic Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

Recommended for Gasoline and Diesel vehicles, including those equipped with turbocharged engines.

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.5
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-36

Package (Liters) 1L, 4L, 5L, 20L, 208L

10W-40

API SL/CF
ACEA A3/B4

DESCRIPTION

ZENON ECO 10W-40 is a fuel-efficient Semi Synthetic Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

Recommended for Gasoline and Diesel vehicles, including those equipped with turbocharged engines.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.875
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15.3
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Package (Liters) 1L, 4L, 5L, 20L, 208L

15W-40

API SL/CF
ACEA A3/B4



DESCRIPTION

ZENON ECO 15W-40 is a fuel-efficient Semi Synthetic/mineral Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.875
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15.5
Viscosity Index	ASTM D2270	-	135
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-30

Package (Liters) 1L, 4L, 5L, 20L, 208L

20W-50

API SL/CF

DESCRIPTION

ZENON ECO 20W-50 is a fuel-efficient Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.880
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	19.5
Viscosity Index	ASTM D2270	-	128
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-24

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Package (Liters) 1L, 4L, 5L, 20L, 208L

SAE40 | API SL/CF



DESCRIPTION

ZENON ECO SAE 40 is an engine oil formulated from high-quality base oils and advanced additive technology. With its extra-thick oil film and superior high-temperature stability, it provides maximum wear protection in engines operating under severe conditions. This oil is particularly suitable for older engines, motorcycles, performance vehicles, and heavy duty diesel applications requiring SAE 40.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Customer Benefits

- Exceptional wear protection under extreme load and heat
- Strong oil film for high-stress, high-temperature operation
- Excellent thermal and oxidation stability
- Controls sludge and deposit formation for longer engine life
- Reduced oil consumption in older and high-mileage engines

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.880
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	14.5
Viscosity Index	ASTM D2270	-	110
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-21

Package (Liters) 1L, 4L, 5L, 20L, 208L

SAE50 | API SL/CF

DESCRIPTION

ZENON ECO SAE 50 is an engine oil formulated from high-quality base oils and advanced additive technology. With its extra-thick oil film and superior high-temperature stability, it provides maximum wear protection in engines operating under severe conditions. This oil is particularly suitable for older engines, motorcycles, performance vehicles, and heavy duty diesel applications requiring SAE 50.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Gasoline and Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.



Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.880
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	19.5
Viscosity Index	ASTM D2270	-	128
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-24

Customer Benefits

- Exceptional wear protection under extreme load and heat
- Strong oil film for high-stress, high-temperature operation
- Excellent thermal and oxidation stability
- Controls sludge and deposit formation for longer engine life
- Reduced oil consumption in older and high-mileage engines

Package (Liters) 1L, 4L, 5L, 20L, 208L

Heavy Duty Diesel Engine Oil (HDDEO)

Heavy Duty Protection

Built for Tough Conditions



5W-30

API CK-4
ACEA E9



DESCRIPTION

ZENON 5W-30 is a fully synthetic and synthetic engine oil designed for both diesel engines operating under severe conditions with high-quality base oils and advanced additive technology, it provides excellent wear protection, high thermal stability, and superior detergency to keep engines clean and efficient.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.2
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Package (Liters) 1L, 4L, 5L, 20L, 208L

5W-40

API CK-4
ACEA E9

DESCRIPTION

ZENON 5W-40 is a fully synthetic and synthetic engine oil designed for diesel engines operating under severe conditions with high-quality base oils and advanced additive technology, it provides excellent wear protection, high thermal stability, and superior detergency to keep engines clean and efficient.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Recommended for modern Diesel passenger vehicles.
- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Customer Benefits

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

Package (Liters) 1L, 4L, 5L, 20L, 208L



10W-30

API CJ-4
ACEA E7/E9



DESCRIPTION

ZENON 10W-30 is a synthetic multi-grade engine oil designed for diesel engines operating under severe conditions with high-quality base oils and advanced additive technology, it provides excellent wear protection, high thermal stability, and superior detergency to keep engines clean and efficient.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Heavy-duty diesel engines requiring 10W-30
- Mixed fleet operations (trucks, buses, construction equipment, diesel powered coastal vessels, generator sets and farm equipment and light commercial vehicles).
- Suitable for engines operating in high-temperature environments.

Customer Benefits

- Outstanding wear protection for extended engine life
- Excellent piston deposit and sludge control
- High oxidation stability for longer oil life
- Strong viscosity retention under severe conditions
- Reliable performance across a wide temperature range

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.6
Viscosity Index	ASTM D2270	-	145
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Package (Liters) 1L, 4L, 5L, 20L, 208L

10W-40

API CJ-4
ACEA E7/E9

DESCRIPTION

ZENON 10W-40 is a synthetic engine oil designed for diesel engines operating under severe conditions with high-quality base oils and advanced additive technology, it provides excellent wear protection, high thermal stability, and superior detergency to keep engines clean and efficient.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- For heavy-duty diesel engines requiring 10W-40.
- Suitable for mixed fleets and high-temperature environments.

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.875
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15.2
Viscosity Index	ASTM D2270	-	145
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33

Customer Benefits

- Outstanding wear protection for extended engine life
- Excellent piston deposit and sludge control
- High oxidation stability for longer oil life
- Strong viscosity retention under severe conditions
- Reliable performance across a wide temperature range

Package (Liters) 1L, 4L, 5L, 20L, 208L



15W-40

API CI-4
ACEA E7



DESCRIPTION

ZENON 15W-40 is a synthetic/semi synthetic/mineral multi-grade engine oil designed for diesel engines operating under severe conditions with high-quality base oils and advanced additive technology, it provides excellent wear protection, high thermal stability, and superior detergency to keep engines clean and efficient.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Heavy-duty diesel engines requiring 15W-40
- Mixed fleet operations (trucks, buses, construction equipment, diesel powered coastal vessels, generator sets and farm equipment and light commercial vehicles).
- Suitable for engines operating in high-temperature environments.

Customer Benefits

- Outstanding wear protection for extended engine life
- Excellent piston deposit and sludge control
- High oxidation stability for longer oil life
- Strong viscosity retention under severe conditions
- Reliable performance across a wide temperature range

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.875
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	15.5
Viscosity Index	ASTM D2270	-	135
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-30

Package (Liters) 1L, 4L, 5L, 20L, 208L

20W-50

API CI-4
ACEA E7

DESCRIPTION

ZENON 20W-50 is a high quality, mineral engine oil formulated for Diesel engines operating under severe driving conditions. Its thicker viscosity provides a strong lubricating film that ensures excellent wear protection, reduced oil consumption, and reliable performance in high-temperature environments. It is particularly suitable for older vehicles, motorcycles, and engines operating in hot climates.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- High-mileage diesel engines require 25W-60.
- Performance engines operate under severe conditions.
- Ideal for hot climates, high loads, and extended driving.

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.880
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	19.5
Viscosity Index	ASTM D2270	-	120
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-27



Customer Benefits

- Enhanced fuel economy for eco-friendly vehicles Diesel engines.
- Rapid cold-start protection to minimize wear at startup
- Superior wear resistance
- Low volatility to reduce oil consumption and emissions
- Excellent deposit control ensuring long engine life

Package (Liters) 1L, 4L, 5L, 20L, 208L

25W-60

API CF



DESCRIPTION

ZENON 25W-60 is a Mineral engine oil specially formulated to deliver exceptional protection for engines operating under extreme temperature conditions. Its extra-thick oil film provides outstanding wear resistance, minimizes oil consumption, and ensures stable lubrication in high-stress environments. It is ideal for older, high mileage diesel engines, motorcycles, and performance vehicles requiring maximum protection.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- High-mileage diesel engines require 25W-60.
- Older vehicles with higher oil consumption.
- Motorcycles and performance engines operate under severe conditions.
- Ideal for hot climates, high loads, and extended driving.

Customer Benefits

- Extra-strong lubricating film for maximum wear protection
- Excellent resistance to high-temperature oxidation and oil breakdown
- Reduces oil consumption in older and high-mileage engines
- Protects against deposits, sludge, and varnish build-up
- Ensures reliable performance in severe driving and extreme climates

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.885
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	25.6
Viscosity Index	ASTM D2270	-	120
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-24

Package (Liters) 1L, 4L, 5L, 20L, 208L

SAE 50

API CF

DESCRIPTION

ZENON SAE 50 is an Engine oil formulated from high-quality Mineral base oils and advanced additive technology. With its extra-thick oil film and superior high-temperature stability, it provides maximum wear protection in engines operating under severe conditions. This oil is particularly suitable for older engines, performance vehicles, and heavy-duty diesel applications requiring SAE 50.

WIDE RANGE & MULTI-PURPOSE APPLICATIONS

- Heavy-duty diesel engines in trucks, buses, and off-road equipment.
- Diesel engines require SAE 50 monograde oil.
- Racing and high-performance engines operating at elevated temperatures

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.880
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	19.5
Viscosity Index	ASTM D2270	-	120
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-18

Customer Benefits

- Exceptional wear protection under extreme load and heat
- Strong oil film for high-stress, high-temperature operation
- Excellent thermal and oxidation stability
- Controls sludge and deposit formation for longer engine life
- Reduced oil consumption in older and high-mileage engines

Package (Liters) 1L, 4L, 5L, 20L, 208L



+971 4 5728818

www.zenonpetroleum.ae

info@zenonpetroleum.ae

Hamriyah Free Zone, Sharjah, United Arab Emirates



Made in UAE